## Shanghai Jiameng International Trading Co., Ltd



4F,Yindong Plaza,No.58 Xinjinqiao RD. Pudong(201206) Shanghai China Tel: +86-21-6165 6998 Fax: +86-21-6165 6995 www.melec.com.cn

# 1kV Heat Shrinkable Cable Accessories

MELEC 1kV heat shrinkable cable accessories are suitable for 0.6/1.0(1.2) kV, insulated with PVC, XLPE and PE polymeric cables. Kits cover a wide range of cable sizes and varying cable constructions.

These accessories can be equipped with either crimping or mechanical lugs and connectors. MELEC mechanical lugs and connectors can be easily installed by a socket spanner without the need of crimping tools. Besides, they can reduce stock requirement because of their wide span range.

#### **Features**

- Compact dimensions
- Hot melting adhesive provides advanced sealing and insulating performance.
- Excellent corrosion resistance
- UV resistance and weathering resistance
- Halogen-free
- Superior electrical and mechanical properties

#### **Standard**

EN 50393

#### **Performance**

Test	Requirements		
AC voltage withstand(in air)	4kV, 1 min. No failure.		
Insulation resistance(in air)	≥50MΩ		
Impact at ambient temperature (only for joints)	A 4kg block dropped onto the accessory from a height of 1 m; Immersed for a minimum of 3h in water with depth of 1m		
AC voltage withstand(immersed) (only for joints)	4kV, 1 min. No failure.		
Insulation resistance(immersed) (only for joints)	≥50MΩ		
Heating cycle(in air)	Heat the conductor to 75°C-95°C, 63 times in air. No failure.		
Heating cycle(in water)	Heat the conductor to 75°C-95°C, 63 times in water. No failure.		
AC voltage withstand(in water)	4kV, 1 min. No failure.		
Insulation resistance(in water)	≥50MΩ		




4F,Yindong Plaza,No.58 Xinjinqiao RD. Pudong(201206) Shanghai China Tel: +86-21-6165 6998 Fax: +86-21-6165 6995 www.melec.com.cn

# **1kV Heat Shrinkable Termination Accessories**

# **Application**

MDD is suitable for multicore, unarmoured cables.



Cores	Туре	Cross-section (mm²)	Min. Dia over Insulation A (mm)	Max. Dia over Lugs (mm)	Recommended Cable Lugs
4-core	MDD-4-01-A	10-35	4.6	14.0	AU AUS CALB-N JTLL
	MDD-4-01-B	50-95	9.3	22.0	
	MDD-4-01-C	120-185	14.2	28.5	
	MDD-4-01-D	240-300	20.4	36.0	
	MDD-4-01-E	300-400	25.7	38.5	

Note: JTLL mechanical lug is suitable for cross-section from 10 to 300mm². Please consult MELEC sales for more details about cable lugs.

### **Standard Package List**

Items	Selection	
CABLE LUG		
HEAT SHRINKABLE INSULATION BREAKOUT	•	
HEAT SHRINKABLE TUBING	•	
HEAT SHRINKABLE TUBING	•	
PHASE TUBING	•	
WATERPROOF SEALING MASTIC	•	
PVC TAPE		
EMERY CLOTH		
CLEANING KIT		
CLEANING CLOTH		
UNDERSHIRT CLOTH GLOVES		
INSTALLATION INSTRUCTION	•	
PACKAGE LIST		

Note: ■ The marked items are basically required.

□ MELEC also provides customized set. Just tick on for your needs. Please consult MELEC sales for more details.